BERS 4.1 INFORMATION CHECKLIST green at heart **CLIENT DETAILS Qld Energy Ratings CLIENT NAME:** QUEENSLAND ENERGY RATINGS **ENERGY EFFICIENCY ASSESSORS** PH: FAX: PO Box 995 Smithfield QLD 4878 EMAIL: (P) 07 4038 3558 (F) 07 4038 3557 PROJECT ADDRESS: ASSESSORS: ANDREW BARRETT 0414 660 399 Assessor No 40101 **ROD HACKETT** 0420 988 991 POSTAL ADDRESS energyrate@green-at-heart.com.au www.green-at-heart.com.au This completed checklist is to accompany all BERS ratings. Please mark boxes with an X. If more than one material is to be used, place 1 in the box for first alternative and 2 for the second alternative. Plans required: - Site Plan, Floor Plans, Elevations, Window Schedule, Electrical Plan (downlights & fans) Section showing insulation (if applicable) **GENERAL:** YES NO 2 SETS OF PLANS PROVIDED FOR ASSESSMENT TRUE NORTH INDICATED ON PLANS COUNCIL TO WHICH PLANS ARE TO BE LODGED PRIVATE CERTIFIER TERRAIN (select one) Exposed Suburban Open Protected **EXTERNAL WALLS: WALL TYPE INSULATION TYPE WALL COLOUR** Weatherboards Concrete block None Light Medium Double Brick Fibre Glass R1.5 Fibre Glass R2.0 **Texture Board** Dark 200mm Hebel Fibre Glass R2.5 Powerpanel Foil lined plasterboard Metal cladding Reflective foil batts **Brick Veneer** Sisalation Aircell (type) Other (Specify) **INTERNAL WALLS: WALL TYPE** Plasterboard on studs Hebel 100mm Conc. Block 200mm Conc. Block 150mm 90mm concrete block Other (Specify) Mud brick **FLOORS FLOOR COVERINGS INSULATION TYPE FLOOR STRUCTURE** None Carpet None Concrete slab R1.0 Vinvl Susp. slab Ceramic tiles R1.5 Timber Timber R2 0 Other Timber on concrete Sisalation 2nd storey floor Styrene 20mm Cork

Other (Specify)

WINDOWS FRAME TYPE Timber Aluminium Alumin.with thermal bro Steel LOUVRES Timber Glass Aluminium	eak]	Single glaz Double glaz Double glaz Double glaz	ed clear ed reflective ed toned		
Curtains - open weave Curtains - close weave Curtains with pelmets Heavy drapes Heavy drapes and pelr Holland blinds Venetian blinds	,		EXTERNAI Roller shutt Canvas aw Outdoor ve Louvres Flyscreens Security Sc	rning netians	SS	
Note: Please indicate clear	ly on the drawings any	pergolas, sunsh	ades, eaves	or other externa	al sunshading device	es .
CEILINGS TYPE Plasterboard Timber lining Concrete		INSULATIO R1.0 R1.5 R2.0	N TYPE]	R2.5 R3.0 R3.5]
ROOFING TYPE Sheet metal Concrete tiles Terracotta tiles Metal tile SKYLIGHTS TYPE		INSULATIO None R1.0 R1.5 Foil and R1. Sisalation	.0 batts		COLOUR Light Medium Dark ROOF VE	NTILATED
Single glazed clear Single glazed opal		Double glaz Double glaz				
HOT WATER SYSTEM Solar- gas boost (Insta Solar- gas boost (Stora Gas (Instantaneous) Gas-storage (High Effic Electric Storage (Heat Gas-storage (Low effic	ntaneous) age) ciency) pump)				ntinuous) [^] rage OP2)	
CEILING FANS Living Bedrooms Size	900mm 1200mm			AIRCONDIT Living Bedrooms	TIONING	
LIGHTING Plan Attached showing 80% fluorescent lightin						

NOTE: If your building product or material is not listed here please provide the name, manufacturer and thermal characteristics such as U value, R value, shading coefficient, reflectance, absorptance etc to the Assessor.

THIS FORM WILL BE SUBMITTED TO THE CERTIFIER OR AUTHORITY AS PART OF THE OFFICIAL RATING ACCOMPANIED BY A FORM 15 AND ENERGY EFFICIENCY CERTIFICATE

 $\hbox{@}\,2009$ This document is copyright and no part may be reproduced by any process without the express permission of the author